

10K DUCTILE IRON Y TYPE STRAINER FLANGED ENDS

KITZ Fig : 10FDYBF

Sizes : 1/2~12inch(15~300mm)

SCREWED CAP, FLAT FACE FLANGED ENDS.

Standards :

- End to End : KITZ STANDARD
- End Connection : JIS B2239 10K
- Wall Thickness : KITZ STANDARD

Test Standard : KITZ St'd-2

Approvals : 1/2~12inch(15~300mm)

Standards : 1/2~12inch(15~300mm)

Dimensions

SIZE(inch/mm)		L	H	Approx (kg)
1/2	15	125.0	57.0	1.5
3/4	20	140.0	62.0	2.0
1	25	150.0	77.0	3.2
1 1/4	32	170.0	90.0	4.5
1 1/2	40	190.0	100.0	5.2
2	50	230.0	138.0	8.9
2 1/2	65	305.0	207.0	16
3	80	360.0	237.0	21
4	100	415.0	279.0	33
5	125	465.0	321.0	39
6	150	515.0	367.0	74
8	200	580.0	461.0	99
10	250	680.0	534.0	155
12	300	800.0	623.0	248

Material

Part Name	Material	Remark
BODY	DUCTILE IRON	FCD-S
CAP	FORGED BRASS	C3771

Specifications


10K DUCTILE IRON Y TYPE STRAINER FLANGED ENDS

End Connection : JIS B2239 10K, Sizes : 1/2~12inch(15~300mm),

BODY Material: DUCTILE IRON, CAP Material: FORGED BRASS, KITZ Fig : 10FDYBF

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.

[Fig Detail Page](#)

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.

KITZ CORPORATION Tokyo Shiodome Building, 1-9-1, Higashi-Shimbashi, Minato-ku, Tokyo 105-7305, Japan
<https://www.kitz.com/en>

© KITZ Corporation. All Right Reserved.

ISO 9001
 CERTIFIED
 Since 1989