

10K DUCTILE IRON WAFER TYPE CHECK VALVE

KITZ Fig：10SWZU
Sizes：2～18inch(50～450mm)
WITH BY-PASS, RUBBER SEAT
Standards：
・End to End：KITZ STANDARD
・End Connection：WAFER TYPE (JIS 10K)
・Wall Thickness：KITZ STANDARD
Test Standard：KITZ St'd-2
Approvals： 2～18inch(50～450mm)
Standards： 2～18inch(50～450mm)





Dimensions

SIZE(inch/mm)		L	H	D	Approx (kg)
2	50	56.0	162.0	70.0	2.1
21/2	65	56.0	168.0	70.0	1.8
3	80	59.0	175.0	70.0	3.3
4	100	66.0	187.0	70.0	4.4
5	125	72.0	201.0	70.0	6.1
6	150	78.0	221.0	80.0	8.8
8	200	96.0	248.0	80.0	15
10	250	109.0	299.0	90.0	25
12	300	145.0	328.0	90.0	37
14	350	184.0	337.0	90.0	56
16	400	191.0	367.0	90.0	78
18	450	204.0	395.0	90.0	111

Material

Part Name	Material	Remark
BODY	DUCTILE IRON+NBR	FCD-S+NBR
STEM	STAINLESS STEEL	SUS420J2
DISC	STAINLESS STEEL	A351 Gr.CF8/SCS13A

Specifications

10K DUCTILE IRON WAFER TYPE CHECK VALVE
End Connection：WAFER TYPE (JIS 10K),Sizes：2～18inch(50～450mm),
BODYMaterial:DUCTILE IRON+NBR, STEMMaterial:STAINLESS STEEL,
DISCMaterial:STAINLESS STEEL,KITZ Fig：10SWZU

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.

Fig Detail Page

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.

© KITZ Corporation. All Right Reserved.