

CLASS 125 CAST IRON Y TYPE STRAINER FLANGED ENDS

KITZ Fig : 125FCY

Sizes : 2~14inch(50~350mm)

BOLTED COVER, FLAT FACE FLANGED ENDS.

Standards :

- End to End : KITZ STANDARD
- End Connection : ASME B16.1 CLASS 125
- Wall Thickness : KITZ STANDARD

Test Standard : KITZ St'd-2

Approvals : 2~14inch(50~350mm)

Standards : 2~14inch(50~350mm)

Dimensions

SIZE(inch/mm)		L	H	Approx (kg)
2	50	250.0	157.0	8.9
2 1/2	65	285.0	207.0	15
3	80	315.0	237.0	18
4	100	370.0	278.0	32
5	125	420.0	321.0	48
6	150	490.0	367.0	73
8	200	570.0	457.0	114
10	250	680.0	536.0	171
12	300	800.0	625.0	240
14	350	950.0	741.0	348

Material

Part Name	Material	Remark
BODY	CAST IRON	FC200
COVER	CAST IRON	FC200

Specifications

CLASS 125 CAST IRON Y TYPE STRAINER FLANGED ENDS

End Connection : ASME B16.1 CLASS 125, Sizes : 2~14inch(50~350mm),

BODY Material: CAST IRON, COVER Material: CAST IRON, KITZ Fig : 125FCY

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.



[Fig Detail Page](#)

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.

KITZ

KITZ CORPORATION Tokyo Shiodome Building, 1-9-1, Higashi-Shimbashi, Minato-ku, Tokyo 105-7305, Japan
<https://www.kitz.com/en>

© KITZ Corporation. All Right Reserved.

ISO 9001
CERTIFIED
 Since 1989