
10K DUCTILE IRON BALL VALVES ,WITH ELECTRIC ACTUATOR

KITZ Fig : EXH200-10STBF
Sizes : 1/2～8inch(15～200mm)
FULL BORE,FLANGED ENDS.
Standards :
・End to End : ASME B16.10 CLASS 150
・End Connection : JIS B2239 10K
・Wall Thickness : KITZ STANDARD
Test Standard : KITZ St'd-2
Approvals : 1/2～8inch(15～200mm)
Standards : 1/2～8inch(15～200mm)





Dimensions

SIZE(inch/mm)		L	H	Actuator	Approx (kg)
1/2	15	108.0	287.0	1	7.2
3/4	20	117.0	290.0	1	7.8
1	25	127.0	298.0	1	9.2
11/4	32	140.0	301.0	2	13
11/2	40	165.0	332.0	2	14
2	50	178.0	339.0	2	16
21/2	65	190.0	409.5	3	25
3	80	203.0	418.5	3	27
4	100	229.0	441.5	3	40
5	125	356.0	551.0	4	60
6	150	394.0	576.0	4	76
8	200	457.0	630.0	4	110

Material

Part Name	Material	Remark
BODY	DUCTILE IRON	FCD-S
BODY CAP	DUCTILE IRON	FCD-S
STEM	STAINLESS STEEL	403SS
BALL	STAINLESS STEEL	304SS

Specifications

10K DUCTILE IRON BALL VALVES,WITH ELECTRIC ACTUATOR
End Connection : JIS B2239 10K,Sizes : 1/2～8inch(15～200mm),
BODYMaterial:DUCTILE IRON, BODY CAPMaterial:DUCTILE IRON,
STEMMaterial:STAINLESS STEEL, BALLMaterial:STAINLESS STEEL,KITZ Fig :
EXH200-10STBF

※Images are for illustrative purposes only. The actual product may differ.

※For details, please refer to the submitted drawing.

Fig Detail Page

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.

© KITZ Corporation. All Right Reserved.